

# Innovative into the Future – BOY Injectioneering





## Product Range BOY injection molding machines

#### Your advantages:

•	Maximum	flexibility
---	---------	-------------

- Small installation surface
- Optimum production conditions
- · Large clamping dimensions
- Flexible application of mould
- Intuitive control
- Easy operation
- · Minimum power consumption
- · Low cooling capacity

Machine type/ Clamping force		Clearance between tie bars	max. shot weight (PS)
BOY XXS 6.93 US tons		6.3 inch / 8.1 inch diagonal	0.49 oz
BOY XS / XS E 11.0 US tons		6.3 inch / 8.1 inch diagonal	0.49 oz
BOY 25 E 27.5 US tons		10 inch	2.45 oz
BOY 35 E 38.5 US tons		11 x 10 inch (h x v)	2.45 oz
BOY 50 E 55.0 US tons		14.2 x 13.2 inch (h x v)	5.56 oz
BOY 60 E 66.0 US tons		14.2 x 13.2 inch (h x v)	5.56 oz
BOY 80 E 88.0 US tons		16.9 x 14.2 inch (h x v)	5.56 oz
BOY 100 E 110.0 US tons	- 15 To 15 T	16.9 x 14.2 inch (h x v)	9.29 oz
BOY 125 E 137.5 US tons		18.50 x 16.93 inch (h x v)	10.91 oz

### **Dimensions in the** compact classe

The range of BOY is convincing

- · Most comprehensive range of servo hydraulic injection molding machines up to 137,5 US tons
- · Cantilevered two-platen clamping system
- · Efficient servo-motor pump drive
- EconPlast technology

- Economic and efficient operation
- · High reliability and operating stability
- · Intelligent control software for intuitive operation
- · Small installation surface
- · Low machine hourly rates

## **Product Range**

### BOY insert molding machines (\*parting line injection)

Machine type/ Clamping force		Clearance between tie bars	max. shot weight (PS)
BOY XS V 11.0 US tons		6.3 inch / 8.1 inch diagonal	0.26 oz
BOY 25 E VV 27.5 US tons		10 inch	2.45 oz
BOY 25 E VH* 27.5 US tons	ALE THE PARTY OF T	10 inch	2.45 oz
BOY 35 E VV 38.5 US tons		11 x 10 inch	2.45 oz
BOY 35 E HV* 38.5 US tons		11 x 10 inch	2.45 oz
BOY 35 E VH* 38.5 US tons		11 x 10 inch	2.45 oz
BOY 60 E VV 66.0 US tons		14.2 x 13.2 inch	5.56 oz

#### Your advantages:

- Insert molding machines with clamping forces of 11.0, 24.2, 27.5, 38.5 and 66.0 US tons
- Exceptionally small space requirements
- Ergonomic design
- Fixed lower clamping plate prevents the inserted parts from slipping
- Ideal options for extension and automation
- Perfect control due to intuitive operation

Machine concepts of insert molding machines









For more than 40 years, BOY manufactures versatile insert molding machines with **vertically arranged clamping unit** which can be used for molding parts inserted.

The mature designs are the result of many years of experience with the basic concept of a **two-platen clamping unit** excellently suitable for this.

With this basic concept, the BOY insert molding machines are constructed **exceptionally ergonomically convenient**.








Unit







Drive Control

Multi-Component

**Automation** 

E-Drive

## **Product Range**

## BOY injection units for multi-component

#### Your advantages:

- Separate hydraulic drive unit and control.
- Available with different injection units.
   Plasticizing volumes up to 8.66 in<sup>3</sup>, as well as injection pressures up to 45,370 psi are possible.
- The controls of both machines communicate with each other via special interface.
- Thus, flexible operation of the machine in innumerable options of application is possible in the area of the multicomponent injection molding.

Machine type		injection unit	max. shot weight (PS)
BOY 2C XS		SP 14	0.26 oz
		SP 11	0.14 oz
		SP 16	0.20 oz
BOY 2C S		SP 45	0.98 oz
		SP 56	0.66 oz
		SP 81	0.98 oz
		SP 96	2.45 oz
BOY 2C M		SP 205	5.34 oz











You would like to learn more about BOY injection molding machines?



Data and Equipment (complete overview)



Competence brochure



**Boy Machines, Inc.** 199 Philips Road Exton, Pennsylvania 19341 Phone: (610) 363-9121 Fax: (610) 363-0163 sales@boymachines.com www.boymachines.com



